

COFLEXIP HOSE

- Manufactured by TechnipFMC
- Certificate of Service by OEM – September 2021
- Internal diameter: 3"
- Length: 75ft
- Working pressure: 15,000 psi
- Test pressure: 22,500 psi
- Max Flow rate: 15m/second
- DNV certified skid
- Applications:
 - Fracturing and acidizing
 - Cementing
 - Drilling fluids
 - Brines and solvents
 - Nitrogen and nitrified



Figure 1 reel shown on the pict not included. Hose is stored in a DNV frame

- Chemical compatibility

Fluid	Concentration	0°F	75°F	150°F	200°F	250°F
Hydrochloric acid HCl	30%	S	S	S	S	S
Hydrofluoric acid HF	7.5%	S	S	S	S	S
Xylene C6 H4 (CH3)2	100%	S	S	S	S	S
Methanol CH3OH	100%	S	S	S	S	S
Glycol	100%	S	S	S	L	L
Zinc bromide ZnBr2	saturated	S	S	S	S	S
Calcium bromide CaBr2	Saturated	S	S	S	S	S
Calcium chloride CaCl2	Saturated	S	S	S	S	S
Methane CH4	100%	S	S	S	S	S
Diesel	100%	S	S	S	S	S
Crude oil	100%	S	S	S	S	S
Sodium hydroxide NaOH	50%	S	S	L	NR	NR
Hydrogen sulfide H2S	<20%	S	S	S	S	S

S: Satisfactory NR: Not Recommended L: Limited use F: Forbidden