

HWO AND SNUBBING 340K UNIT

These units are designed and custom built to perform live and dead well interventions on both land & offshore.

ADVANTAGES

- Utilized Offshore & Onshore
- Environmentally Friendly
- Experienced Well Control Personnel
- Reduced Footprint
- Efficient Mobilization / Demobilization
- Eliminates the Need for Kill Fluids

SERVICES

- Conventional Workovers
- Completion/Recompletion
- Fishing and Milling
- Clean Out Operations
- Plug & Abandonments
- And Much More



341 Specifications

Unit type	Stand Alone 4-Leg Jack
Max pull capacity	340,000 lbs.
Max push capacity	160,000 lbs.
Rotary/2 Speed Application	12,000/15,000/22,000 ft/lbs. Available
Stroke	10' Stroke
Jack Bore Size	11"
Pipe range	2 3/8" to 7 5/8"
Gin pole	38-60 ft Height
Pipe Handling	Failsafe/Counter Balance Winch: 1500lbs Rated Failsafe/Utility Winch: 10,000lbs Rated
Work window	6' Inside Height 14" Through Bore
Power slips	Hydra Rig Slip Bowls
Power tongs	Third Party Rental
Rated working pressure	5k 10k and 15k BOPs and Circulating System Available

SNUBBING APPLICATIONS

- Well control
- Live well fishing jobs
- Tubing cleanouts (barium/asphaltene/paraffin/sand) removal
- Live well completions
- Thru tubing fishing / milling
- High pressure pumping
- Damaged / leaking completion repair
- Live well pressure milling
- Packer & plug fishing
- Installation of plugs, packers and liners
- Underbalanced drilling
- Perforating
- Well killing



WORKOVER APPLICATIONS

- Completions / recompletions / tubing change-out (single / dual)
- ESP change-outs
- Gravel packs
- Casing cutting
- Plug & abandonment
- Section Milling
- Side tracking
- Wash jobs
- Straddle packers
- Zone isolation
- Pumping services
- Spotting cement
- Pipe recovery
- Squeeze Jobs